ДЕКЛАРАЦИЯ ХАРАКТЕРИСТИК КАЧЕСТВА

МЕДНАЯ ПРОДУКЦИЯ

Медные СНЕГОЗАДЕРЖАТЕЛИ ORIMA®

Уникальный код идентификации типа изделия и характеристики:
Медные снегозадержатели прошли статическое испытание согласно стандарту SS 8313667 с испытательной нагрузкой 5 кН/м. Конструкция и размеры изделий соответствуют требованиям SS-стандарта.

Наименование	Код изделия	Руководство по монтажу
Круглая трубка 2,5 м	31013KI	LE2CU
Крепление на фальц	35643KI	

Предусмотренное применение строительного изделия
Постоянно установленный на несущих конструкциях наклонных крыш снегозадержатель, предотвращающий падение и движение скопившегося снега, защищающий покрытие кровли, а также людей, сооружения и оборудование возле здания.

Медные КРОВЕЛЬНЫЕ МОСТИКИ ORIMA®

Уникальный код идентификации типа изделия и характеристики:
Медные кровельные мостики прошли статическое испытание согласно стандарту EN 516:2006 тип B с испытательной нагрузка 1,5 кН, основанной на теоретической допустимой нагрузке одного пользователя (100 кг) с фактором безопасности. Тест имитирует одного человека, идущего по кровельному мостику в нормальных условиях. Конструкция и размеры изделия соответствуют требованиям стандарта EN.

Наименование	Код изделия	Руководство по монтажу
Полотно кровельного моста 2,97 м	30033KI	KS3CU
Полотно кровельного моста 2,47 м	30023KI	
Полотно кровельного моста 1,21 м	30013KI	
Фиксатор мостика	30064KI	
Крепление на фальц	35643KI	

Предусмотренное применение строительного изделия
Постоянно установленные на несущих конструкциях наклонных крыш мостики на кровлю (строительные изделия), на которые можно наступать или ходить по ним при осмотре, техническом обслуживании и ремонте сооружений на крыше.

Медные ЛЕСТНИЦЫ-КРЫЛЬЦО ORIMA®

Уникальный код идентификации типа изделия и характеристики:
Медные лестницы-крыльцо прошли статическое испытание согласно стандарту EN 12951:2004 тип B с испытательной нагрузкой 1,5 кН, основанной на теоретической допустимой нагрузке одного пользователя (100 кг) с фактором безопасности. Тест имитирует одного человека, идущего по лестнице на крыше в нормальных условиях. Конструкция и размеры изделия соответствуют требованиям стандарта EN.

Наименование	Код изделия	Руководство по монтажу
Полотно лестницы-крыльца 1,2 м	22013KI	KR2CU
Полотно лестницы-крыльца 2,4 м	22033KI	
Крепление на фальц	22153KI	

Предусмотренное применение строительного изделия
Постоянно установленные на несущих конструкциях наклонных крыш несъемные металлические лестницы, на которые можно наступать или ходить по ним для осмотра, технического обслуживания и ремонта оборудования, установленного над поверхностью крыши. Конструкции C2 можно использовать для крепления индивидуальных средств защиты от падения.

Производитель
Orima-Tuote Oy, Kankaantie 6, FI-16100 Orimattila +358 3 872 100, **www.orima.fi**, myynti@orima.fi

Характеристики изделий, указанных в данном документе, соответствуют заявленным выше. Данная декларация характеристик качества выпущена при полной ответственности производителя.

Подписано от имени производителя:

Orimattila, 1.10.2018

Mikko Ahonen, генеральный директор

ORIMA-TUOTE OY
Kankaantie 6, FI-16300 ORIMATTILA
Тел. +358 3 872 100

www.orima.fi

ISO 9001 BUREAU VERITAS Certification
№ FIHSK10155078A

PERFORMANCE LEVELS, WARRANTY

Copper
ROOF WALKWAY, ROOF STEP LADDERS, SNOW FENCES

Copper ROOF WALKWAY

Unique identification code of the product-type and the declared performance

The roof walkway made of copper is tested according to EN 516:2006 type B standard with 1,5 kN static test load based on a theoretical working load of one user (100 kg) with safety factor. The test simulates one person walking along the roof walk way at normal conditions. Design and dimensions of the product meet the requirements of EN-standard.

Name	Product code	Installation guide
Roof walkway 2.97 m	30033KI	KS3CU
Roof walkway 2.25 m	30203KI	
Roof walkway 1.21 m	30014KI	
Upper supporter	30064KI	
Seam fastener set	35643KI	

Intended use of building product

Roof access (building products) permanently fixed to the load-bearing construction of pitched roofs, to stand or to walk on during inspection, maintenance and repair of facilities on the roof.

Copper ROOF STEP LADDERS

Unique identification code of the product-type and the declared performance

The roof step ladder made of copper is tested according to EN 12951:2004 type B standard with 1,5 kN static test load based on a theoretical working load of one user (100 kg) with safety factor. The test simulates one person walking along the roof step ladder at normal conditions. Design and dimensions of the product meet the requirements of EN-standard.

Name	Product code	Installation guide
Roof step ladder 1.2 m	22013KI	KR2CU
Roof step ladder 2.4 m	22033KI	
Seam fastener set	22153KI	

Intended use of building product

Permanently fixed ladders made of metal which are permanently installed on the load-bearing construction of pitched roofs and which may be stepped or walked on for purposes of inspection, maintenance and repair of equipment installed above the roof surface.

Copper SNOW FENCES

Unique identification code of the product-type and the declared performance

The snow fence made of copper is tested according to SS 8313667 standard with 5 kN/m static test load. Design and dimensions of the product meet the requirements of SS-standard.

Name	Product code	Installation guide
Round tube 2.5 m	31013KI	LE2CU
Seam fastener set	35643KI	

Intended use of building product

Horizontal barrier permanently fixed to the construction of pitched roofs, prevent accumulated snow from falling and moving, protect the coating of the roof and persons, constructions and equipment near the building.

Name of Manufacturer

Orima-Tuote Oy, Kankaantie 6, FI-16100 Orimattila
+358 3 872 100, **www.orima.fi**, myynti@orima.fi

The performance of the products indentified in this document is conformity with the declared performance. These performance levels are issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Orimattila, 1.10.2018

Mikko Ahonen, CEO